

**LED 60 Watts Canopy Light with Sensor** **OLS Item # CAN-DLC-T24-60W**



Wattage	60W
Initial Lumens	4,999 Lumens
Input Voltage	120-277V/50-60 Hz
CRI	73
CCT	5000K
Power Factor	0.95
THD	≤15%
Driver Type	Constant Current / Type 1
Luminaire Life	50,000HRS
Surge Protector	4KV inside of Driver
Dimension	14.4"x14.4"x9"
Weight	12.1 lbs. (5.5kg)
Operating Temperature	-30°F~+130°F
Humidity	≤95%
IP Rating	IP 54 Suitable for Wet Location
Main Material	Die casting housing, High strength PC lens anti-static powder painting
Certification	ETL,cETL,DLC,FCC,RoHs
Warranty	5 Year Manufacturer Warranty
Reports Available	LM79,LM80

- \* **New Title 24 Compliant Canopy Light**
- \* **Great Light for parking garage and canopies**
- \* **This light will replace a 250 MH fixture. It meets the new building code for occupancy and dimming.**

**Adjustable Dimming Function to Comply With New Building Code Title 24.**

Operating voltage	120~277VAC
Switched power	400W@120VAC; 800W@230VAC; 1000W@277VAC (capacitive load)
Standby power	<1W
Detection area	10%/50%/75%/100%, can be customized
Hold time	5s/30s/1min/5min/10min/20min/30min
Standby period	0s/10s/1min/5min/10min/30min/1h/
Standby dimming level	10%/20%/30%/50%
Daylight threshold	2~50Lux/disable
Sensor principle	Microwave motion detector
Microwave frequency	5.8GHz+/-75MHz
Microwave power	<0.2mw
Detection range	Max. (OxH): 12m x 6m
Detection angle	30°~150°
Mounting height	Max.6m
Operating temperature	-30°F~+150°F

