


PH: (559) 500-1986 FX: (559) 513-8505 **855 GO2-LED2** (462-5332)

LED Wall Pack:

60 Watts 4,849 Lumens





| SPECIFICATIONS | OLS MODEL # WP-DLC-FL-60W-5K-HL |
|------------------------|---|
| Wattage Rated: | 65 Watts Isolux Plot |
| LED Light: | 60 Watts |
| Replaces: | Up to 250 watt Metal Halide |
| Lighting System: | Cree LED's 3 |
| Input Voltage: | AC120-277V 2 |
| CCT: | 5000K-5700K |
| Inicial Lumen Output | 4,849 |
| Frequency Range: | 50Hz~60Hz |
| Driver: | Constant current class 1 |
| Surge Protector: | 4KV inside of driver ² |
| CRI: | 75Ra 3 |
| Power Factor: | >0.95 |
| THD: | < 15 % |
| Luminare Life: | 50,000 hours |
| Operating Temperature: | -30°F to +130°F Distance in units of mount height (6M) Max Cd |
| Humidity: | <95% Polar Candela Distribution 2,300 2,300 180° 170° 160° 150° 140° |
| Housing Material: | Heavy-duty cast aluminum housing |
| r | ust and corrosion proof; polyester power coating. |
| Glass Material: | High light transmittance borosilicate glass |
| Dimensions: | 18.2" x 9" x 9.4" |
| Weight: | 14.8 Lbs. |
| Manufacturer Warranty: | 5 Years |
| Main Certification: | ETL, cETL, FCC RoHS, LM79, LM80, DLC |

Product Enhancement may result in specification changes without notice. Contact us for the lates information.